

CODE: MBK19-1350AF-EXT

ERP: 0135514

## Trolley Fire Extinguisher 135Lt Foam Trolley

Trolley Fire Extinguisher, 135Lt, with 5m Discharge Hose The external cartridge contains Nitrogen (N2) as propellant gas



### CHARACTERISTICS

Capacity	135Lt
Extinguishing Agent	132,5L water + 2,7L KB301/14
Operating Temperature	+5~+60 °C
Max Allowable Pressure	20 bar
Test Pressure	30 bar
Volume of Equipment	147 lt
Cylinder Height	1295±4 mm
Cylinder Diameter	407±1 mm
Cylinder Neck Thread	M74x2
Cylinder Material	HP295
Valve Material	CuZn40Pb2
Safety Valve	22-27 bar
Approx. Dimensions	1700x600 mm
Paint Finish	RAL 3000
Packaging Details	1 pc.



EN1866



Issue Date: 23/12/2019

Information may change

**FACTORY:** AKROTIRI, CHANIA, P.C. 73100, TEL. +30 2821063222, FAX: +30 28210 66260

**CENTRAL EXHIBITION:** 96-98 M. MPOTSARI str. P.C. 73136, CHANIA, GREECE, TEL. +30 28210 91561, FAX +30 28210 91644

**ATHENS DISTRIBUTION CENTER:** MAGOULA - ASPROPIRGOS, P.C. 19300, TEL. +30 210 4614006, FAX +30 210 5595986

**N.GREECE DISTRIB. CENTER:** 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL. +30 2310 785668, FAX +30 2310 574793

**CENT. & EAST CRETE DISTRIB. CENTER:** P<sup>1</sup> str. INDUSTRIAL ZONE OF HERAKLION - CRETE, P.C. 71601, TEL./FAX +30 2810 333151

[www.mobiak.gr](http://www.mobiak.gr)